

Valvole di sicurezza
 Safety valves
 Soupapes de sécurité
 Válvulas de seguridad

Temperatura max: 90°C - 195°F
 Max temperature: 90°C - 195°F
 Température maxi: 90°C - 195°F
 Temperatura máx: 90°C - 195°F



ACCIAIO INOX
 STAINLESS STEEL



CODICE PART NR.	MODELLO MODEL	PRESSIONE MAX MAX PRESSURE		PORTATA FLOW		Attacco pompa Port size	Scarico By-pass	PESO WEIGHT	
		BAR	PSI	l/min	GPM			Kg	lbs
86.1677.00.2	VS 280 (AISI 303)	280	4000	80	21	N°2 1/2 BSP - F	1/2 BSP - F	1.21	2.7
86.1678.00.2	VS 400 (AISI 303)	400	5800	80	21	N°2 1/2 BSP - F	1/2 BSP - F	1.21	2.7
86.1679.00.2	VS 500	500	7250	80	21	1/2 BSP - F	1/2 BSP - F	1.42	3.1
86.1779.00.2	VS 180	180	2610	200	53	3/4 BSP - F	1/2 BSP - F	0.82	1.8
86.1680.00.2	VS 200	200	2900	450	119	1"1/4 BSP-F	1"1/4 BSP-F	3.8	8.4